

Tel: +27 12 803 8595  
Fax: +27 12 803 8462  
Customer care line: 086 1554 321  
e-mail: timberlife@icon.co.za  
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD  
REG No 2000/017132/07



# TimberLife

PO Box 73117, Lynnwood Ridge, 0040  
31 Axle Street  
Silverton Ext 52  
Pretoria, South Africa

## PRODUCT DATA SHEET

## Furni-Wax

- Product Name:** FURNI-WAX
- Product Type:** PENETRATING WOOD STABILIZING AND WATER REPELLENT WAX FINISH FOR UNCOATED FURNITURE AND JOINERY
- Description:** FURNI-WAX is a deep penetrating, solvent-based formulation that provides a protective and aesthetic treatment for uncoated, interior wooden furniture and joinery. It contains a special blend of light coloured water repellent waxes that stabilizes and prevents water absorption into the wood.
- FURNI-WAX provides a satin-like semi-gloss finish that nourishes and enhances the natural beauty of the wood. Regular application of FURNI-WAX will ensure that your wooden furniture and joinery always remain in a sound and aesthetic condition.
- Ideal for use** on any uncoated interior timbers where a natural sheen finish is preferred. Not recommended for use on exterior timbers except if pretreated with **CTX 108**.
- Active Ingredients:** Blend of waxes in an organic solvent carrier
- Physical Characteristics:**
- |                |   |                             |
|----------------|---|-----------------------------|
| Appearance     | - | Off white semi-liquid paste |
| Solubility     | - | Solvent borne               |
| Density @ 20°C | - | ± 0,79 kg/l                 |
- Use Restriction:** Not recommended for use on exterior timbers and previously coated timber surfaces. Remove old coatings and sand surface before application.
- Application:** Use a clean soft cloth to apply FURNI-WAX in light, short circular movements, ensuring thorough and even distribution of the wax. Leave the wax on for 1 to 2 hours (but not for longer than 3 hours) to allow for absorption into the wood. Remove excess FURNI-WAX with a clean soft cloth and buff well in between coats to leave a natural smooth polished finish. Apply further coats until the desired finish has been achieved. Simply re-apply further coats as and when desired.
- Application Rate:** 5m<sup>2</sup> - 10m<sup>2</sup> per l per coat.
- Dilution Rates:** Ready for use. DO NOT DILUTE.
- Storage:** Storage temperatures should not exceed 40°C. Keep container sealed.
- Packaging:** 1l, 5l, 20l, 25l and 200l containers.
- Caution:** The product is flammable. Avoid open flames.