

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa



PRODUCT DATA SHEET

KhuniDip

Product Name:	KHUNIDIP									
Product Type:	INDUSTRIAL WATER REPELLENT AND WOOD STABILIZING SEALER									
Description:	<p>KhuniDip is an oil/wax-based penetrating sealer that protects raw (uncoated) wood against water ingress, surface degradation and contamination. The high quality blend of drying oils and water repellent wax components deeply penetrates, stabilizes and nourishes the wood. It therefore acts as a transit stabilizer and protective sealer that prevents excessive checking and splitting of pre-manufactured timbers during transport and storage and also repels waste splashes during building construction. KhuniDip dries to a clear matt finish that does not flake or peel.</p> <p>KhuniDip can be tinted to various shades of brown by using “DipTints SB” that contain UV resistant transparent iron oxide pigments and provide a durable, high quality stained finish, e.g. Mahogany, Golden Brown, Deep Brown, Teak, Oak, Meranti, Oregon, etc.</p> <p>KhuniDip can also be used as a final finish on wood provided that a second and preferably a third coat is applied after installation. It is, however, recommended that two coats Satinwood 28/28 Base be applied as a final, high quality exterior finish after installation as it contains additional fungicides and insecticides that provide added protection against mould growth, fungal staining and insect attack.</p>									
Active Ingredients:	Drying oils and Waxes and Iron oxides in organic solvent carrier									
Physical Characteristics:	<table><tr><td>Appearance</td><td>-</td><td>Transparent amber colour and/or tints of brown</td></tr><tr><td>Solubility</td><td>-</td><td>Solvent borne</td></tr><tr><td>Density @ 20°C</td><td>-</td><td>± 0,79 – 0,81 kg/ℓ</td></tr></table>	Appearance	-	Transparent amber colour and/or tints of brown	Solubility	-	Solvent borne	Density @ 20°C	-	± 0,79 – 0,81 kg/ℓ
Appearance	-	Transparent amber colour and/or tints of brown								
Solubility	-	Solvent borne								
Density @ 20°C	-	± 0,79 – 0,81 kg/ℓ								
Use Restriction:	Not to be used on previously coated timber surfaces. Remove old coatings and sand surface before application.									
Application:	Brush, spray or dip. MIX WELL BEFORE USE.									
Application Rate:	4m ² - 8m ² per ℓ per coat (depending on the type of timber).									
Dilution Rates:	Ready for use. DO NOT DILUTE.									
Storage:	Storage temperatures should not exceed 40°C. Keep container sealed.									
Packaging:	25ℓ, 200ℓ and 1000ℓ containers.									
Caution:	The product is flammable. Avoid open flames. Avoid eye splashes and prolonged skin contact.									