

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07



TimberLife

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa

PRODUCT DATA SHEET

Satinwood 28/28 Base

Product Name:	SATINWOOD 28/28 Base		
Product Type:	PENETRATING EXTERIOR WATER REPELLENT WOOD FINISH		
Description:	<p>SATINWOOD 28/28 Base is a solvent-based finish that contains penetrating water repellent oil and wax components to nourish and protect wood against the elements when exposed to exterior conditions. SATINWOOD 28/28 Base contains a fungicidal additive that provides added surface protection to wood against mould growth and fungal discolouration. It also contains an additional insecticide to provide surface protection against wood borer and termite attack. SATINWOOD 28/28 Base enhances the natural beauty of the wood and dries to a satin-like, translucent finish that does not flake or peel. Most suitable for applications such as wooden decks, doors, window frames, cladding, log homes, outdoor furniture etc.</p> <p>Can be tinted to shades of brown: Mahogany, Oregon, Teak, Oak, Dark Oak, Golden Brown and Walnut (Only use Timberlife SOLV-TINTS that contain high quality, colour fast transparent iron oxide pigments)</p> <p><i>Satinwood 28 is recommended for Softwoods and Hardwoods of high porosity.</i> <i>Satinwood 28 Base is recommended for Hardwoods of low porosity.</i></p>		
Active Ingredients:	Drying oils, Waxes and Fungicide plus Insecticide		
Physical Characteristics:	Appearance	-	Transparent amber colour
	Solubility	-	Solvent borne
	Density @ 20°C	-	± 0,82 – 0,87 kg/ℓ
Use Restriction:	Not to be used on previously coated timber surfaces. Remove old coatings and sand surface before application.		
Application:	Brush, spray or dip. Mix contents before use. Apply a second coat 24 hours after applying the first coat. Apply a third coat if necessary. Wipe any excess product from the surface.		
Application Rate:	5m ² - 10m ² per ℓ per coat (depending on the timber type).		
Dilution Rates:	Ready for use.		
Storage:	Storage temperatures should not exceed 40°C. Keep container sealed.		
Packaging:	1ℓ, 5ℓ, 20ℓ, 25ℓ and 200ℓ containers.		
Caution:	Flammable. Avoid open flames. Avoid eye splashes and prolonged skin contact.		