

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07



TimberLife

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa

PRODUCT DATA SHEET

UltraDeck

Product Name: ULTRADECK

Product Type: PENETRATING SEALER AND HIGH BUILD WOOD FINISH FOR EXTERIOR AND INTERIOR USE

Description: **UltraDeck** is a solvent-borne sealer that penetrates the wood and builds to a protective, semi-gloss finish with good wear resistance. It is particularly suitable for use on exterior timbers such as wooden decks and walkways.

UltraDeck contains a unique blend of high quality resins, drying oils, water repellent wax components and UV resistant transparent iron oxide pigments. These ingredients are dissolved in a formulated solvent carrier system to deeply penetrate, nourish and stabilize the wood and ensure protection against water ingress and UV degradation caused by sunlight exposure. It dries to an aesthetic finish that enhances the natural colour and beauty of the wood.

UltraDeck is available in the following shades of brown: Teak, Golden Brown, Deep Brown and Oak.

Ideal for use on wooden decks, walkways and all other exterior timbers such as stairs, balustrades, garden furniture, etc. where a hard wearing, semi-gloss finish is preferred.

Active Ingredients: Resins, Drying oils, Waxes and UV resistant transparent iron oxide pigments.

Physical Characteristics:	Appearance	-	Dark liquid with different shades of brown
	Solubility	-	Solvent borne
	Density @ 20°C	-	± 0,85 kg/l

Use Restriction: Not to be used on previously coated timber surfaces. Remove old coatings before application.

Application: Brush, spray or dip methods. In case of non-porous hardwoods, dilute the first coat 1:1 with mineral turpentine or white spirits. Mix contents before use. Apply a liberal first coat and allow to dry for at least 4 to 6 hours. Sand lightly, apply a second coat and spread evenly. Allow to dry for 24 hours before applying a final coat.

Application Rate: 6m² - 12m² per l per coat (depending on timber type).

Dilution Rates: Ready for use.

Storage: Storage temperatures should not exceed 40°C. Keep container sealed.

Packaging: 1l, 5l, 20l, 25l and 200l containers.

Caution: Flammable. Avoid open flames.