

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (Pty) Ltd
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa



PRODUCT DATA SHEET

CompoSeal

Product name:	COMPOSEAL		
Product type:	TRANSPARENT EXTERIOR/INTERIOR SEALER FOR WOOD – PLASTIC COMPOSITE PRODUCTS		
Description:	<p>CompoSeal is a high performance, emulsion-based (solvent free) sealer for use on Wood-Plastic Composite decking and other exposed surfaces. The coating provides water repellency and a colourless sheen finish that protects Wood-Plastic Composite products from oil stains and grime.</p> <p>CompoSeal contains acrylic resins plus UV absorbers and light stabilizers that provide flexibility to the coated film and protect the coating against the harmful effect of sunlight.</p> <p><i>Available as a clear transparent sealer than can also be tinted with Aqua-Tints water-borne stain additives.</i></p>		
Active ingredients:	Acrylic resins, UV absorbers and light stabilizers.		
Physical Characteristics:	Appearance	- Milky white liquid	
	Solubility	- Waterborne	
	Density @ 20°C	- ± 1,01 - 1,02 kg/ℓ	
Use restriction:	For industrial use and household use.		
Dilution rates:	MIX WELL BEFORE USE. Ready for use. Do not dilute.		
Application:	Apply a thin coast using a paint or roller brush. Allow to dry for 4 to 6 hours and apply a second coat thinly and evenly. Allow at least 24 hours curing time before using decking surfaces.		
Application rates:	10 to 20 m ² /ℓ per application depending on the porosity of the surface.		
Storage:	Storage temperate should not exceed 50°C. Keep container tightly closed.		
Packaging:	1ℓ, 5ℓ, 20ℓ, 25ℓ and 200ℓ containers nett.		
Note:	Wash equipment with water immediately after use.		