

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (Pty) Ltd
REG No 2000/017132/07



TimberLife

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa

PRODUCT DATA SHEET

CTX 108 PWT

Product Name:	CTX 108 PWT								
Product Type:	INSECTICIDAL AND FUNGICIDAL SURFACE TREATMENT FOR SEASONED TIMBER								
Description:	<p>CTX 108 PWT is a ready-for-use organic solvent-based solution containing specifically blended insecticidal and fungicidal active ingredients that provides a greenish surface treatment for protection of seasoned timber against wood borer and termite attack as well as discolouring fungi and mould growth.</p> <p>CTX 108 PWT contains a high level of insecticide to provide long term protection and also to control and eradicate wood boring insects in infested timber. On application, the organic solvent provides a degree of penetration of the active ingredients into the wood structure and ensures rapid drying on the treated surfaces. After drying, any coating/finish can be applied on the treated wood surface.</p>								
Active Ingredients:	Synthetic pyrethroid and organosulphur compound.								
Physical Characteristics:	<table><tr><td>Appearance</td><td>- Greenish transparent liquid</td></tr><tr><td>Solubility</td><td>- Aromatic solvents</td></tr><tr><td>Density</td><td>- $\pm 0,88$ kg/l</td></tr><tr><td>Flammability</td><td>- Highly flammable</td></tr></table>	Appearance	- Greenish transparent liquid	Solubility	- Aromatic solvents	Density	- $\pm 0,88$ kg/l	Flammability	- Highly flammable
Appearance	- Greenish transparent liquid								
Solubility	- Aromatic solvents								
Density	- $\pm 0,88$ kg/l								
Flammability	- Highly flammable								
Use Restriction:	Only to be used and applied in accordance with label warnings, precautions and directions for use.								
Application:	Apply to clean, dry timber surfaces before application of a final wood coating/finish. Ensure that all surfaces are thoroughly covered by using either brush-on, dip or spray application methods.								
Application Rate:	4 - 8m ² /l, depending on surface smoothness								
Dilution Rates:	Ready for use. Do not dilute CTX 108 PWT								
Storage:	Store in closed containers at temperatures below 40°C.								
Packaging:	1l, 5l, 20l, 25l containers and 200l steel drums								
Note:	Caution: Poisonous. Avoid ingestion, skin contact and prolonged inhalation of vapours. Thoroughly wash hands and contaminated skin with soap and water after use. Highly flammable. Avoid open flames.								