

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa



PRODUCT DATA SHEET

Khuni Sealer

Product Name: KHUNI SEALER

Product Type: CONTRACTORS WOOD STABILIZING OIL

Description: **KHUNI SEALER** is an oil/wax-based penetrating sealer that protects raw (uncoated) wood against water ingress, surface degradation and contamination. The high quality blend of drying oils and water repellent wax components deeply penetrates, stabilizes and nourishes the wood. It therefore acts as a transit stabilizer and protective sealer that prevents excessive checking and splitting of pre-manufactured timbers during transport and storage and also repels waste splashes during building construction.

KHUNI SEALER can also be used as a final finish on wood provided that a second and preferably a third coat is applied 24 hours after applying the first coat. It, however, does not provide protection against fungal and insect attack.

Should a durable, high quality exterior finish be required, it is recommended that **SATINWOOD 28/28 Base** be applied as a final coat as it contains additional wood stabilizing agents as well as fungicides and insecticides that provide added protection against mould growth, fungal staining and insect attack. **KHUNI SEALER** dries to a clear matt finish.

Active Ingredients: Drying oils and Waxes in organic solvent carrier

Physical

Characteristics:	Appearance	-	Transparent amber colour
	Solubility	-	Solvent borne
	Density @ 20°C	-	± 0,79 – 0,89 kg/l

Use Restriction: Not to be used on previously coated timber surfaces. Remove old coatings and sand surface before application.

Application: Brush, spray or dip. MIX WELL BEFORE USE.

Application Rate: 5m² - 10m² per l per coat. If used as a final finish, apply a second coat and preferably a third coat 24 hours after applying the first coat.

Dilution Rates: Ready for use. DO NOT DILUTE.

Storage: Storage temperatures should not exceed 40°C. Keep container sealed.

Packaging: 1l, 5l, 20l, 25l and 200l containers.

Note: **Caution:** The product is flammable. Avoid open flames.