

Tel: +27 12 803 8595  
Fax: +27 12 803 8462  
Customer care line: 086 1554 321  
e-mail: timberlife@icon.co.za  
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD  
REG No 2000/017132/07



# TimberLife

PO Box 73117, Lynnwood Ridge, 0040  
31 Axle Street  
Silverton Ext 52  
Pretoria, South Africa

---

## PRODUCT DATA SHEET

## Solv-Tints

---

|                                  |   |
|----------------------------------|---|
| <b>Product Name:</b>             | <b>SOLV-TINTS</b>   |
| <b>Product Type:</b>             | <b>INTERIOR/EXTERIOR SOLVENT-BORNE STAIN ADDITIVE</b>   |
| <b>Description:</b>              | <p><b>SOLV-TINTS</b> are organic solvent-based stain additives consisting of high quality transparent iron oxides pigments.</p> <p><b>Ideal for</b> tinting solvent-borne wood coating/finishing products such as “<b>SATINWOOD 28/28 BASE</b>”, “<b>SATINWOOD GLOSS</b>”, “<b>KHUNI SEALER</b>” and “<b>ULTRACARE GOLD</b>” to various shades of brown: Mahogany, Oregon, Golden Brown, Teak, Oak, Dark Oak and. Walnut.</p> <p><b>SOLV-TINTS</b> provide non-leachable, UV resistant and long lasting colours that do not hide the wood grain. Excellent UV protection is also afforded when added to clear wood coating/finishing systems. Can therefore be used for interior and exterior applications.</p> |
| <b>Active Ingredients:</b>       | Transparent iron oxides and organic solvents  |
| <b>Physical Characteristics:</b> | Appearance - Tints of brown   |
|                                  | Solubility - Soluble in organic solvents  |
|                                  | Density @ 20°C - 0,95 - 1,15 kg/ℓ   |
| <b>Use Restriction:</b>          | Only for use with solvent-borne wood coating/finishing products.  |
| <b>Addition:</b>                 | Shake contents well before addition. Add to coating/finishing product and mix well before and during use.   |
| <b>Addition Rate:</b>            | 36g per ℓ (recommended)   |
| <b>Dilution Rates:</b>           | Ready for use   |
| <b>Storage:</b>                  | Storage temperatures should not exceed 40°C. Keep container sealed  |
| <b>Packaging:</b>                | 36g, 180g and 900g containers nett  |
| <b>Note:</b>                     | <b>Caution:</b> The product is flammable  |