

Tel: +27 12 803 8595  
Fax: +27 12 803 8462  
Customer care line: 086 1554 321  
e-mail: timberlife@icon.co.za  
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD  
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040  
31 Axle Street  
Silverton Ext 52  
Pretoria, South Africa



---

## PRODUCT DATA SHEET

## Supro EM

---

<b>Product Name:</b>	<b>SUPRO EM</b>
<b>Product Type:</b>	<b>TIMBER SPLIT AND CRACK PREVENTATIVE TREATMENT</b>
<b>Description:</b>	<p><b>SUPRO EM</b> is a ready-for-use wax emulsion that is compatible with and effectively seals green (freshly cut) timber, particularly the end grain. Upon drying it forms a water resistant coating that prevents excessive checking and end splitting during drying of the timber. <b>SUPRO EM</b> also acts as a highly effective water repellent sealer.</p> <p>It has a milky white appearance and dries to a translucent coating. <b>SUPRO EM</b> is also available with colour additives for visual identification.</p>
<b>Active Ingredients:</b>	Paraffin wax
<b>Physical Characteristics:</b>	Appearance - Milky white liquid Solubility - Dispersible in water Density @ 20°C - 0,95 kg/l
<b>Use Restriction:</b>	For use on freshly cut timber
<b>Application:</b>	The working solution can be applied to timber by brush, dip or spray methods.
<b>Application Rate:</b>	4 - 6m <sup>2</sup> /l
<b>Dilution Rates:</b>	Ready for use (do not dilute SUPRO EM)
<b>Storage:</b>	Storage temperatures should not drop below 5°C or exceed 50°C. Product may require stirring prior to use to ensure uniformity.
<b>Packaging:</b>	25l and 200l nett containers
<b>Note:</b>	For best results, apply SUPRO EM as soon as possible after cutting, especially on the ends