

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07



TimberLife

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa

PRODUCT DATA SHEET

Timber-Tones

Product Name:	TIMBER-TONES
Product Type:	INTERIOR WOOD COLOURING STAIN
Description:	<p>TIMBER-TONES are penetrating wood colouring stains that consist of high quality dyestuffs dissolved in organic solvents.</p> <p>TIMBER-TONES are available in a variety of typical wood shades as well as high intensity colour tones to enhance the natural beauty of the wood grain. After application any wood coating such as “ULTRACARE GOLD”, “COLOR-COTE AM” or “FURNI- FLOOR” can be used as a final protective finish.</p> <p>Ideal for use on all interior timbers such as wooden furniture, wooden floors, doors, skirting boards, cupboards, etc. to stain such timbers to a darker shade before final finishing. Not recommended for use on exterior timbers exposed to direct sunlight.</p>
Active Ingredients:	Dyestuffs and organic solvents
Physical Characteristics:	<p>Appearance - Tints of brown</p> <p>Solubility - Soluble in organic solvents</p> <p>Density @ 20°C - 0,83 - 0,86 kg/ ℓ</p>
Use Restriction:	Not for use on previously coated timber surfaces. Surfaces must be thoroughly cleaned/stripped from waxy oils or varnish-type coatings.
Application:	Brush, spray or dip. Mix contents well before use.
Application Rate:	4m ² - 8m ² per ℓ, depending on type of timber
Dilution Rates:	Ready for use. May be dilute with lacquer thinners if a lighter colour shade is required.
Storage:	Storage temperatures should not exceed 40°C. Keep container tightly sealed
Packaging:	500ml, 1 ℓ, 5 ℓ and 25 ℓ containers nett
Note:	Caution: The product is flammable. Avoid any open flames or sparks. Ensure good ventilation during application. Observe safety precautions on label before use.