

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07



TimberLife

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa

PRODUCT DATA SHEET

TRS 250

- Product Name:** TRS 250
- Product Type:** CLEAR PENETRATING WOOD STABILIZER AND WATER REPELLENT
- Description:** TRS 250 is a penetrating, solvent-based formulation that contains drying oils to stabilize wood from the inside out and also light coloured, water repellent wax components to control water ingress. It dries to a virtually colourless, natural matt finish.
- When exposed to direct sunlight, TRS 250 degrades on the surface and allow the wood to weather to a natural silver-grey colour over time. However, due to its deep penetrating properties, the wood beneath the surface remains nourished and stabilized to control unsightly checking, splitting and warping.
- TRS 250 also contains a fungicidal additive to provide protection against mould growth and fungal discolouration.
- Ideal for use** on timbers where a clear natural matt finish is desired and also on exposed wooden decks and walkways where a natural weathered look is preferred.
- Active Ingredients:** Drying oils, Waxes and a Fungicide in organic solvent carrier
- Physical Characteristics:**
- | | | |
|----------------|---|-------------------------------|
| Appearance | - | Translucent, yellowish liquid |
| Solubility | - | Solvent borne |
| Density @ 20°C | - | ± 0,81 kg/l |
- Use Restriction:** Not suitable for use on previously coated timber surfaces. Remove old coatings and sand surface before application.
- Application:** Brush, roller brush, spray or dip. Mix contents before use. Apply a liberal first coat and allow to dry for approximately 24 hours. Apply a second and third coat if necessary, leave on for about 3 hours and wipe off any excess liquid. Thereafter reapply on an annual basis or when desired.
- Application Rate:** 5m² - 10m² per ℓ per coat.
- Dilution Rates:** Ready for use. DO NOT DILUTE.
- Storage:** Storage temperatures should not exceed 40°C. Keep container sealed.
- Packaging:** 1ℓ, 5ℓ, 20ℓ, 25ℓ and 200ℓ containers.
- Caution:** The product is flammable. Avoid open flames.