

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07



TimberLife

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa

PRODUCT DATA SHEET

UltraCoat

| | | | |
|----------------------------------|---|---|--|
| Product Name: | ULTRACOAT | | |
| Product Type: | HIGH BUILD PENETRATING WOOD SEALER FOR EXTERIOR AND INTERIOR USE | | |
| Description: | <p>UltraCoat is a penetrating, solvent-borne wood sealer that provides a protective high build, semi-gloss finish with good water repellency.</p> <p>UltraCoat contains a unique blend of high quality resins, drying oils and water repellent wax components and can be tinted with UV resistant transparent iron oxide pigments. These ingredients are dissolved in a formulated solvent carrier system to penetrate, nourish and stabilize the wood and ensure protection against water ingress and UV degradation caused by sunlight exposure. It is a high build formulation that dries to an aesthetic finish that enhances the natural colour and beauty of the wood.</p> <p>UltraCoat is available in various shades of brown, e.g. Teak, Golden Brown, Deep Brown, Oak, etc.</p> <p>Ideal for use on wooden window and door frames, doors and all other exterior timbers such as balustrades, garden furniture, etc. where a high build, semi-gloss finish with good flexibility is needed.</p> <p>Note - Not recommended for use on high traffic areas such as wooden decks and walkways</p> | | |
| Active Ingredients: | Resins, Drying oils, Waxes and UV resistant transparent iron oxide pigments. | | |
| Physical Characteristics: | Appearance | - | Dark liquid with different shades of brown |
| | Solubility | - | Solvent borne |
| | Density @ 20°C | - | 0,90 to 0,91 kg/ℓ |
| Use Restriction: | UltraCoat should not to be used on previously coated timber surfaces. Remove old coatings before application. | | |
| Application: | Brush, roller brush or spray methods. In the case of non-porous hardwoods, dilute the first coat 1:1 with mineral turpentine or white spirits. Mix contents well before use. Apply a liberal first coat and allow to dry for at least 4 to 6 hours. Sand lightly, apply a second coat and spread evenly. Allow to dry for 24 hours before applying a final coat. | | |
| Application Rate: | 6m ² - 12m ² per ℓ per coat (depending on timber type). | | |
| Dilution Rates: | Ready for use. | | |
| Storage: | Storage temperatures should not exceed 40°C. Keep container sealed. | | |
| Packaging: | 1ℓ, 5ℓ, 20ℓ, 25ℓ and 200ℓ containers. | | |
| Caution: | Flammable. Avoid open flames. | | |