

Tel: +27 12 803 8595  
Fax: +27 12 803 8462  
Customer care line: 086 1554 321  
e-mail: timberlife@icon.co.za  
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD  
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040  
31 Axle Street  
Silverton Ext 52  
Pretoria, South Africa



## PRODUCT DATA SHEET

## UltraDip

**Product Name:** ULTRADIP

**Product Type:** HIGH BUILD INDUSTRIAL WATER REPELLENT AND WOOD STABILIZING SEALER

**Description:** **UltraDip** is a high build, solvent-based penetrating sealer that protects raw (uncoated) wood against water ingress, surface degradation and contamination. The high quality blend of drying oils, resins and water repellent wax components deeply penetrates, stabilizes and nourishes the wood. It therefore acts as a transit stabilizer and protective sealer that prevents excessive checking and splitting of pre-manufactured timbers during transport and storage and also repels waste splashes during building construction. **UltraDip** dries to a translucent sheen finish that does not flake or peel.

**UltraDip** is also available with UV resistant transparent iron oxide pigments that provide a durable, high quality stained finish, e.g. Mahogany, Golden Brown, Teak, Oak, etc. or blended to specification.

It is recommended that two coats **UltraCare Gold** be applied as a final, high quality exterior wood finish after installation as it contains additional UV absorbers and light stabilizers as well as fungicides and insecticides that provide added protection against UV degradation caused by sunlight exposure as well as mould growth, fungal staining and insect attack.

**Active Ingredients:** Drying oils, Resins and Waxes, with or without Iron oxide pigments in organic solvent carrier

### Physical

<b>Characteristics:</b>	Appearance	-	Transparent amber colour and/or tints of brown
	Solubility	-	Solvent borne
	Density @ 20°C	-	± 0,82 kg/l

**Use Restriction:** Not to be used on previously coated timber surfaces. Remove old coatings and sand surface before application.

**Application:** Brush, spray or dip. MIX WELL BEFORE USE.

**Application Rate:** 5m<sup>2</sup> - 10m<sup>2</sup> per l per coat (depending on the type of timber).

**Dilution Rates:** Ready for use. DO NOT DILUTE.

**Storage:** Storage temperatures should not exceed 40°C. Keep container sealed.

**Packaging:** 25l, 200l and 1000l containers.

**Caution:** The product is flammable. Avoid open flames. Avoid eye splashes and prolonged skin contact. Used cloths may ignite spontaneously – Dispose of in a safe manner or completely submerge in water after use.