

Tel: +27 12 803 8595  
Fax: +27 12 803 8462  
Customer care line: 086 1554 321  
e-mail: timberlife@icon.co.za  
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD  
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040  
31 Axle Street  
Silverton Ext 52  
Pretoria, South Africa



---

## PRODUCT DATA SHEET

## Waksol F

---

<b>Product Name:</b>	<b>WAKSOL F</b>	
<b>Product Type:</b>	<b>INDUSTRIAL TIMBER WATER REPELLENT</b>	
<b>Description:</b>	<p><b>WAKSOL F</b> is a dark green, wax-based water repellent. It is <b>NOT</b> soluble in water. <b>WAKSOL F</b> is compatible with oils, creosote and most other organic-based coatings applied to timber. In some applications it can also act as a mould release agent on timber.</p> <p><b>WAKSOL F</b> can be used in the cement brick industry where timber brick pallets needs protection against water absorption.</p>	
<b>Active Ingredients:</b>	Waxes and oils	
<b>Physical Characteristics:</b>	Appearance	- Dark green viscous liquid
	Solubility	- Soluble in organic solvents
	Density @ 20°C	- ± 0,90 kg/l
<b>Use Restriction:</b>	None	
<b>Application:</b>	Dip or roller brush. Mix contents before use	
<b>Application Rate:</b>	± 0,6 l per m <sup>2</sup> timber surface area. This is however influenced by the type of timber, the moisture content of the timber and application method. Apply ± every 3 months for cement brick pallets depending on production rates on pallets.	
<b>Dilution Rates:</b>	May be diluted with a suitable organic solvent if required	
<b>Storage:</b>	Storage temperatures should not exceed 50°C	
<b>Packaging:</b>	200 l nett steel drums	
<b>Note:</b>	Keep product away from open flames	