

Tel: +27 12 803 8595  
Fax: +27 12 803 8462  
Customer care line: 086 1554 321  
e-mail: timberlife@icon.co.za  
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD  
REG No 2000/017132/07



# TimberLife

PO Box 73117, Lynnwood Ridge, 0040  
31 Axle Street  
Silverton Ext 52  
Pretoria, South Africa

---

## PRODUCT DATA SHEET

## Weatherseal

---

<b>Product name:</b>	<b>WEATHERSEAL</b>
<b>Product type:</b>	Wax emulsion additive for timber treatment with CCA, borates and FLAMBOR.
<b>Description:</b>	<b>WEATHERSEAL</b> is a water miscible wax emulsion for use as a water repellent additive to CCA, borate and FLAMBOR treating solutions. Water repellency provided by <b>WEATHERSEAL</b> impregnation improves dimensional stability of treated timber and reduces checking, splitting and general weathering of timber products exposed to exterior conditions.
<b>Active ingredients:</b>	Paraffin waxes - 450 g/l (min)
<b>Physical Characteristics:</b>	Appearance - Milky white liquid Solubility - Miscible in water Density @ 20°C - ± 0,95 kg/l pH - ± 8,5
<b>Use restriction:</b>	For industrial use only
<b>Dilution rates:</b>	Typically used at <b>WEATHERSEAL</b> volume concentrations ranging from 20 ml/l to 10 ml/l (Please consult label instructions)
<b>Application:</b>	By pressure impregnation of seasoned timber in combination with CCA, borates or FLAMBOR wood preservatives.
<b>Application rate:</b>	4l/m <sup>3</sup> , minimum
<b>Storage:</b>	Storage temperatures should not exceed 35°C - 40°C. Do not allow to freeze.
<b>Packaging:</b>	200l nett plastic drums or bulk delivery
<b>Caution:</b>	<b>WEATHERSEAL</b> concentrate may cause mild irritation of the skin and eyes. Wash off with plenty of water.
<b>Note:</b>	<b>WEATHERSEAL</b> is non-flammable