

Tel: +27 12 803 8595
Fax: +27 12 803 8462
Customer care line: 086 1554 321
e-mail: timberlife@icon.co.za
Website: www.timberlife.co.za

TIMBERLIFE (PTY) LTD
REG No 2000/017132/07

PO Box 73117, Lynnwood Ridge, 0040
31 Axle Street
Silverton Ext 52
Pretoria, South Africa



PRODUCT DATA SHEET

Karbo-Seal Black

Product Name: KARBO-SEAL BLACK

Product Type: EXTERIOR WATER REPELLENT WOOD SEALER

Description: **Karbo-Seal Black** is a dark to black coloured, ready-for-use waxy oil-based water repellent wood sealer for exterior use. It can be diluted with most organic solvents for easier application, improved penetration and a less waxy final finish. Because of the dark brown finish provided by **Karbo-Seal Black**, it is an excellent alternative for carbolineum and creosote without the strong smell and use restrictions.

Please note: **Karbo-Seal Black** does not contain any pesticides. Should additional insecticidal and fungicidal protection be needed, pretreat the timber with **CTX 108**.

Karbo-Seal Black is ideal for use as an affordable water-repellent treatment on exterior timbers such as roof trusses, battens, fascia boards, rough sawn cladding, wooden fences and gates, all wooden poles etc. where a dark, brownish black colour is required.

Active Ingredients: Waxes and oils

Physical Characteristics:

Appearance	- Black viscous liquid
Solubility	- Soluble in organic solvents
Density @ 20°C	- ± 0,89 to 0,91 kg/l

Use Restriction: None

Application: Brush, roller brush, spray-on or dip application methods. Mix content well before use. Heat solution slightly or dilute with an organic solvent if a lower viscosity is required.

Application Rate: 5 to 10 m² per litre, depending on the type of timber, the moisture content of the timber and application method.

Dilution Rates: May be diluted with a suitable organic solvent if required.

Storage: Storage under cool, dry conditions in closed containers.

Packaging: 1, 5 and 25 l net plastic containers and 200 l net steel drums.

Caution: Keep product away from open flames.